

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
7 August 2003 (07.08.2003)

PCT

(10) International Publication Number
WO 03/064844 A1

(51) International Patent Classification⁷: **F02M 25/10**,
25/12

(21) International Application Number: PCT/US02/02168

(22) International Filing Date: 25 January 2002 (25.01.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **WORLD
AIR ENERGY CORPORATION** [US/US]; P.O. Box
309, Nixon, TX 78140-0309 (US).

(71) Applicant and

(72) Inventor: **DAVIDSON, James, G.** [US/US]; 3615 High-
way 79 North, Paris, TN 38242 (US).

(74) Agent: **MAXWELL, Roger, L.**; Jenkins & Gilchrist, P.C.,
Suite 3200, 1445 Ross Avenue, Dallas, TX 75202 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,
NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND APPARATUS FOR MEMBRANE SEPARATION OF AIR INTO NITROGEN AND OXYGEN ELEMENTS FOR USE IN INTERNAL COMBUSTION ENGINES



(57) Abstract: A method and apparatus for reducing the emissions and improving the performance of an internal combustion engine (40). An input air stream is separated into an oxygen-enriched air stream and a nitrogen-enriched air stream. The nitrogen-enriched air stream is received by a holding chamber (35). The oxygen-enriched air and a combustible fuel are provided to a combustion chamber (45) of the internal combustion engine (40) and a combustion process is initiated. After a predefined time delay, a volume of nitrogen-enriched air is provided from the holding chamber (35) to the combustion chamber (45) to be used during the rest of the combustion process.

WO 03/064844 A1